

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
24 December 2003 (24.12.2003)

PCT

(10) International Publication Number
WO 03/106938 A1(51) International Patent Classification⁷: G01G 21/10

(21) International Application Number: PCT/AU03/00745

(22) International Filing Date: 13 June 2003 (13.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PS 2919 13 June 2002 (13.06.2002) AU(71) Applicant (for all designated States except US): CLOSE
THE LOOP TECHNOLOGIES PTY LTD [AU/AU];
Unit 2, 19 Macquarie Drive, Thomastown, VIC 3074 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MORRISS, Stephen
[AU/AU]; 15 John Street, Eltham, VIC 3095 (AU). BAD-
MAN, Graham [AU/AU]; C/-Brentwood Recycling Sys-
tems, 238 Berkeley Road, Unanderra, NSW 2526 (AU).
BADMAN, Jim [AU/AU]; C/-Brentwood Recycling Sys-
tems, 238 Berkeley Road, Unanderra, NSW 2526 (AU).(74) Agent: BALDWIN SHELSTON WATERS; 60 Margaret
Street, Sydney, NSW 2000 (AU).(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR EXTRACTING TONER FROM TONER CARTRIDGES



(57) Abstract: The invention provides a method and apparatus for recycling toner cartridges. A shredder (1) breaks up the toner cartridges into pieces, thereby releasing any toner from within the otherwise substantially sealed cartridges. The toner pieces along with any free toner powder are then fed through a separation stage including a mechanical separator (3) and a trommel separator (4). Each separator employs a sifting screen, which allow smaller particles to fall through the screen while holding back the larger pieces. Both separators agitate the pieces to mobilise the smaller particles. A vacuum extraction system (7) is used to withdraw air from around the cartridge pieces and an air ioniser is included for feeding ionised air into the apparatus to reduce any static electronic charge build up. The toner is removed from the extracted air by a dust collector.

Title: Method and apparatus for extracting toner from toner cartridges

Field of the Invention

The present invention relates generally to recycling of toner cartridges, and more particularly to the separation of materials during the recycling of toner cartridges.

5

Background of the Invention

The invention has been developed primarily for use in extracting toner powder from toner cartridges, and will be described predominantly with reference to this application. It will be appreciated, however, that the invention is not limited to this particular field of use, being also applicable to other applications where separating a powder material from larger pieces is required.

Toner printing technology has been almost universally adopted in photocopiers and computer printers. These devices commonly have an internal reservoir for storing toner powder which is used in the printing process. Initially, these reservoirs were fixed to the machine and required manual refilling by pouring toner from a refill packet. Nowadays, in an attempt to limit direct contact with the messy toner powder, replaceable toner cartridges have largely superseded refillable reservoirs. Cartridges are filled in a factory where the distribution of toner powder can be strictly controlled to minimise and isolate spillage.

The popularity of disposable cartridges has meant the number of cartridges discarded has increased exponentially in recent years. Used cartridges may, in some cases, be recycled and recharged a number of times by a specialist reconditioner. Eventually however, all cartridges are either stripped down for their materials or more often, thrown out altogether. Either of these alternatives presents their own particular problems.

25

The cartridges are generally a combination of thermo-plastic resins and ferrous and non-ferrous metals. These materials are slow to break down naturally and thus present a significant environmental pollutant. In addition, it is rare that toner cartridges are entirely empty when they are replaced. Often 5% to 10% of the toner capacity of the cartridge remains when discarded. This figure can be as high as 100% if the cartridge is faulty, has been superseded or past its use by date. The residual toner also presents a significant environmental hazard when the cartridges are thrown out. However, whilst toner along with the materials which make up the cartridges are recyclable, the nature of toner powder makes stripping the cartridges difficult.

Toner is a very fine powder and will readily become airborne and circulate with airflow. As such it can be easily inhaled and may be a significant health issue with workers. Moreover, as with many fine powders, when airborne, in the right concentration and conditions it can ignite and explode.

Currently the stripping and materials separation of cartridges is carried out manually. This not only places those doing the stripping in a high risk environment, it is also labour intensive and expensive. In modernised countries, which are the greatest users of these printer cartridges, labour cost are high meaning the manual dismantling of cartridges is not cost effective.

It is an object of the present invention to overcome or ameliorate one or more of these disadvantages of prior art, or at least to provide a useful alternative.

Disclosure of the Invention

In a first aspect, the invention provides a method of extracting toner from toner cartridges, said method including the steps of:

breaking up toner cartridges into pieces to release toner from within the cartridges;

- 3 -

passing the cartridge pieces over a sifting barrier so that only particles under a predetermined size pass through the barrier;

agitating the pieces to mobilise the toner;

extracting air from adjacent the pieces to remove airborne particles; and

5 removing toner from the air extracted from adjacent the pieces.

According to another aspect, the invention includes an apparatus for extracting toner from toner cartridges including:

a shredder for breaking up toner cartridges into pieces and to thereby release toner from within the cartridges;

10 a sifting barrier for sifting the cartridge pieces so that only particles under a predetermined size pass through the barrier;

agitation means to agitate the pieces and mobilise the toner;

an extractor for extracting air from around the sifting barrier to remove airborne particles; and

15 a toner collector for recovering toner extracted by the extractor.

Preferably, the invention includes an ioniser for introducing ionised air into the apparatus.

Preferably, the agitating means is a trommel which repeatedly lifts and drops the pieces.

20 Preferably, the trommel includes an inner drum adapted to rotate about its longitudinal axis and an outer cover, the inner drum having a plurality of apertures and functioning as a separation screen so that only particles under a predetermined size pass through the screen and into the outer cover.

Preferably, the sifting barrier is a vibrating screen, substantially enclosed by a casing and more preferably, the extractor extracts air from the casing through the vibrating screen to encourage particles under a predetermined size to pass therethrough.

Preferably, a classification column separates toner powder from impurities.

5

Brief Description of the Drawings

A preferred embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Fig. 1 is a front view of an apparatus for extracting toner from toner cartridges in
10 accordance with the invention;

Fig. 2 is side view of the apparatus shown in Fig. 1;

Fig. 3 is a top view of the apparatus shown in Fig. 1;

Fig. 4 is an partial, enlarged front view of the apparatus shown in Fig. 1; and

Fig. 5 is a side view of a filtering system in accordance with the invention.

15

Preferred Embodiments of the Invention

Referring to the drawings, in general terms the invention provides a method and apparatus for the extracting toner from toner cartridges. While the forgoing description refers to toner cartridges, it will be appreciated that this term is intended to also include
20 refill bottles and vessels.

The apparatus includes a shredder 1 for breaking the toner cartridges into pieces, thereby releasing any toner from within the otherwise substantially sealed cartridges. The toner pieces along with any free toner powder are then fed through a separation stage generally shown as 2 in the figures. The separation stage includes a mechanical
25 separator 3 and a trommel separator 4. Each separator employs a sifting screen,

numbered 5 and 6 respectively, which allow smaller particles to fall through the screen while holding back the larger pieces. Both separators agitate the pieces to mobilise the smaller particles. The mechanical separator provides a high frequency vibration to mobilise the toner, whereas the trommel provides a lower frequency tumbling and rubbing action to liberate the toner from the cartridge pieces.

A vacuum extraction system 7 is used to withdraw air from around the cartridge pieces. This not only has the effect of encouraging the small particles through the screen, but also extracts airborne toner dust and limits the amount of dust that exits the system to the surrounding air. The apparatus further includes an air ioniser (not shown) for feeding ionised air into the apparatus to reduce any static electronic charge build up. The ionised air has the combined effect of reducing the likelihood of sparking and possible subsequent ignition of any airborne toner powder during the shredding stage and moreover, reducing any electric charge attraction between the toner and cartridge pieces further aiding in toner liberation.

To describe the process in greater detail, toner cartridges are collected and transported to the plant for recycling. Before the cartridges are processed, they may be examined to determine statistical information on the origin, number and types of cartridges as well as a checking to ensure that each cartridge is suitable for processing. The examination may be conducted by a manual check of each cartridge or by automatic means. Automatic examination means may include a bar code and bar-code reader system, electronic data chip and reader or knowledge/image database recognition.

Referring to Figure 1, the cartridges are then placed in a hopper 8 which feeds a conveyor belt 9. The conveyor may be substantially enclosed to prevent toner escaping to the air outside the apparatus. The conveyor 9 transports the whole cartridges to the

shredder 1 which includes a shredder hopper 10 situated above the shredder 1. The shredder hopper and shredder, like the conveyor 9 may also be enclosed.

Referring now to Figure 4, the shredder employs twin parallel rollers 11 with intermeshing projections to grind the cartridges into pieces ranging in size from very small chips to pieces not exceeding 25 millimetres in width. The rollers operate at a relatively low speed of around 26 rpm in order to minimise the risk of sparking. The shredding process releases much of the toner from the cartridges however, some toner will adhere to the larger pieces of cartridge due to static charge or mechanical binding.

The toner and pieces of cartridge then drop through the shredder chute 12 and into the mechanical separator 3. The mechanical separator includes a vibrating screen 5 surrounded by a casing 13 at the top that wraps around the lateral sides of the screen to the bottom. A tray 14 is disposed within the casing, underneath the screen. The screen is powered by an electric motor 15, which cycles the screen at around 50Hz. The entire separator 3 is not in direct contact with the rest of the apparatus and is located on springs 16 to isolate its movement. Rubber flanges provide a seal between the shredder and the separator without passing on vibration.

The screen 5 is sloped downwardly at an angle between 5° and 20°, but preferably 10°. This slope combined with the vibration, encourages the cartridge pieces to move gradually over the screen 5 and through the separator 3 toward the separator exit 17. If the angle too small, the pieces will remain in the separator too long and slow the process unnecessarily, if the angle is too steep they will pass through too quickly and are not subjected to sufficient vibration. The high frequency vibration has the effect of mobilising the toner powder, detaching it from the larger plastic pieces. This allows the small particles including toner powder and other small impurities such as chips of plastic produced during shredding to drop through the screen 5 and into the tray 14 at the

bottom of the separator 3. The tray is sloped at an angle similar to the screen such that the particles are channelled down the tray and into the duct 18.

As shown in Figure 3, the duct 18 is in turn, connected by ducting 19 to the vacuum extraction system 7, which withdraws air from the tray 14 of the separator 3.

5 Ionised air is also introduced into the casing to pass over the pieces and through the screen. The passage of air transports the small particles through the ducting 19 and into the toner collector 20. In addition, a low static pressure is formed within the casing 3 by the vacating air. This low pressure creates a continuous airflow into the separator from outside which reduces the amount of powder and dust escaping from the separator and
10 into the surrounding air. The small particles are carried by the airflow through the screen 5, into the tray 14 and duct 18.

Before reaching the toner collector 20 the withdrawn air, toner and small impurities are passed into a classification column 21 shown in Figure 5. The classification column 21 separates the very small and light powder particles from the
15 relatively larger, small toner chips and impurities. The ducting 19 from the separator 3 is connected to the bottom of a vertical column or chimney 22. The chimney has a bin 23 at the bottom, below the ducting join 24. As shown by arrow a, the small particles are drawn into the chimney along with the airflow. The airflow being regulated to have sufficient velocity to draw the small light toner dust up the chimney 22, and into the
20 toner collector 20, whilst not being strong enough to lift the comparatively heavier chips. The required airflow rate is dependent on a range of factors including toner mass and size, chip mass and size, and air humidity, density and temperature. The chips fall down the chimney 22 and are collected in the bin 23 at the bottom of the chimney. In this way most of the impurities can be effectively filtered from the toner before it enters the toner
25 collector 20.

The toner collector 20 may be a standard or modified dust extraction/collector unit where the small toner particles are removed from the air and collected in storage bin 25. Further processing of these particles to purify the toner dust may be necessary at a later stage.

5 Any pieces, which do not fall through the screen, are passed from the mechanical separator exit 17 into the trommel 4. The floor of the trommel is set below the level of the floor of the vibrating screen so that the pieces of cartridge along with any powder must drop down into the trommel. As is known in the art, the trommel includes an axially rotating, perforated inner drum 26 and a surrounding outer cover 27. The inner
10 drum is orientated so that its bottom side is sloped slightly downwardly, approximately 10 degrees off horizontal. This slope and the rotation advance the cartridges pieces through the drum 26 toward the trommel exit 28. The drum rotates so that the pieces are raised up the side of the drum 26 before falling back to the bottom. This tumbling action may be enhanced by small protrusions and longitudinal ribs on the inside surface of the
15 drum which catch and raise the pieces. The agitation motion of the trommel, along with the initial drop into the trommel, acts to mobilise any small particles.

The inner drum 26 also acts as a separation screen; the perforations allow smaller particles to pass through drum 26 wall and into the space between it and the outer cover 27. At the bottom of the cover, an air duct 29 is connected to the extraction system 7 by
20 ducting 30 to withdraw the particles along with air from within the cover. As before, the airflow has the effect of encouraging small particles to pass from the inner drum 26 into the cover as well as reducing the likelihood that airborne particles will escape from the trommel.

It will be appreciated that the trommel may be replaced by an alternative means for agitating the cartridge pieces. However, alternative device should provide a similar tumbling and rubbing action.

In addition ionised air may also be injected into the trommel.

5 The small particles collected from the trommel 4 are passed into the classification column and filtered in the toner collector 20 and stored.

The remaining larger cartridge pieces, now substantially excluding toner dust and small particles exit the trommel 4 onto a second conveyor 31. At the end of the conveyor 31 a magnetic head pulley 32 and twin chute assembly 33 substantially
10 separates the ferrous metal components from the other components into bins, 34 and 35 respectively.

The conveyor 9, shredder 1, casing of the mechanical separator and cover of the trommel may all be individually and together, substantially sealed, such that the process from start to exit of the trommel is isolated from the surrounding air. In this way,
15 airflow into and out of the system can be regulated.

Additional air ducts can be added to extract air from the system or its surroundings at any point where particle concentration may be high. For instance, air may be drawn from the conveyor 9 and/or shredder hopper 10 through ducting 36 and 37 respectively. In this way, the air surrounding the invention remains substantially free of
20 particles, or at least in concentrations which are not hazardous to workers and do not present a risk of explosion.

In alternative embodiments, or compressed air is injected into the separators or shredder chute. The compressed air is directed to blow the powder from the larger pieces.

It will be appreciated that the invention provides a largely automated method and apparatus for extracting toner powder from toner cartridges. The invention enables the materials of cartridges to be recycled quickly, in a cost effective manner. Moreover, particulate concentration in the surrounding air is significantly reduced, eliminating the potential hazards of dust inhalation by workers and the risk of explosion. In all these respects, the invention represents practical and commercially significant improvement over the prior art.

Although the invention has been described with reference to specific examples it will be appreciated by those skilled in the art that the invention may be embodied in many other forms.

Claims:

1. A method of extracting toner from toner cartridges, said method including the steps of:
 - breaking up toner cartridges into pieces to release toner from within the
 - 5 cartridges;
 - passing the cartridge pieces over a sifting barrier so that only particles
 - under a predetermined size pass through the barrier;
 - agitating the pieces to mobilise the toner;
 - extracting air from adjacent the pieces to remove airborne particles; and
 - 10 removing toner from the air extracted from adjacent the pieces.
2. A method according to claim 1 including the further step recovering the toner for recycling.
3. A method according to claim 1 or claim 2 including the further step of introducing ionised air adjacent the pieces.
- 15 4. A method according to any one of the proceeding claims whereby agitating the pieces involves repeatedly lifting and dropping the pieces.
5. A method according to any one of the proceeding claims whereby a trommel is used to agitate the pieces.
6. A method according to claim 5 whereby the trommel includes an inner drum
- 20 adapted to rotate about its longitudinal axis and an outer cover, the inner drum having a plurality of apertures and functioning as a separation screen so that only particles under a predetermined size pass through the screen and into the outer cover.
7. A method according to claim 6 whereby air is extracted from within the outer cover to encourage particles under a predetermined size to pass through the apertures in
- 25 the inner drum.

8. A method according to any one of the proceeding claims whereby the sifting barrier is a vibrating screen.
9. A method according to claim 8 whereby the vibrating screen is substantially enclosed by a casing and air is extracted from the casing through the vibrating screen to encourage particles under a predetermined size to pass therethrough.
10. A method according to claim 8 or 9 whereby the vibrating screen slopes downwardly on an angle from the horizontal of between 5° and 20°, to encourage the pieces to move over the screen.
11. A method according to any one of the proceeding claims whereby the cartridges are broken up by a shredder.
12. A method according claim 11 whereby the shredder employs twin rollers to break up the cartridges.
13. A method according claim 12 whereby air is extracted from the shredder.
14. A method according to any one of the proceeding claims including the further step of filtering air extracted from adjacent the pieces to remove particles under a predetermined size.
15. A method according to claim 14 whereby the air extracted from adjacent the pieces is passed though a classification column to separate toner powder from impurities.
16. A method according to any one of the proceeding claims including the further step of collecting the cartridge pieces for recycling.
17. A method according to claim 16 including the further step of sorting the cartridge pieces into ferrous metals and non-metals/plastics.
18. An apparatus for extracting toner from toner cartridges including:
a shredder for breaking up toner cartridges into pieces and to thereby release toner from within the cartridges;

a sifting barrier for sifting the cartridge pieces so that only particles under a predetermined size pass through the barrier;

agitation means to agitate the pieces and mobilise the toner;

an extractor for extracting air from around the sifting barrier to remove
5 airborne particles; and

a toner collector for removing toner from the air extracted by the
extractor.

19. An apparatus according to claim 18 including an ioniser for introducing ionised air into the apparatus.

10 20. An apparatus according to claim 18 or claim 19 wherein the agitating means repeatedly lifts and drops the pieces.

21. An apparatus according to any one of claims 18 to 20 wherein the agitating means is a trommel.

22. An apparatus according to claim 21 wherein the trommel includes an inner drum
15 adapted to rotate about its longitudinal axis and an outer cover, the inner drum having a plurality of apertures and functioning as a separation screen so that only particles under a predetermined size pass through the screen and into the outer cover.

23. An apparatus according to claim 22 wherein the extractor extracts air from within the outer cover to encourage particles under a predetermined size to pass through the
20 apertures in the inner drum.

24. An apparatus according to any one claims 18 to 23 wherein the sifting barrier is a vibrating screen.

25. An apparatus according to claim 24 wherein the vibrating screen is substantially enclosed by a casing and the extractor extracts air from the casing through the vibrating
25 screen to encourage particles under a predetermined size to pass therethrough.

26. An apparatus according to claim 24 or 26 wherein the vibrating screen slopes downwardly on an angle from the horizontal of between 5° and 20°, to encourage the pieces to move over the screen.
27. An apparatus according to any one of claims 18 to 26 the shredder employs twin
5 rollers to break up the cartridges.
28. An apparatus according claim 27 wherein the extractor extracts air from the shredder.
29. An apparatus according to any one of claims 18 to 28 including a classification column to separate toner powder from impurities.
- 10 30. An apparatus according to any one of claims 18 to 29 including the further step of collecting the cartridge pieces for recycling.
31. An apparatus according to claim 30 including a magnetic separator for sorting the cartridge pieces into ferrous metals and non-metals/plastics.




FIG.1




FIG.2




FIG. 3




FIG. 4




Fig. 5.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU03/00745

A. CLASSIFICATION OF SUBJECT MATTER		
Int. Cl. ⁷ : G01G 21/10		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) DWPI, JAPIO: Int. Cl. ⁷ and keywords: G01G 21/10; toner, developer; recover, recycle, separate, reuse, reusable; shred, break, broken, crush, grind, destroy, demolish, shatter, smash, B02C; sift, screen, filter, sieve, strain, B07B; vibrate, agitate, shake, shook; cartridge. Espacenet, USPTO: toner, cartridge, crush, grind, shred, sift, sieve, screen.		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6311904 B1 (LETURMY et al) 6 November 2001 Whole document (especially fig 1)	1, 2, 4-18, 20-31
X	JP 2002-079125 A (SATO TEKKO CO LTD) 19 March 2002 See machine translation [online], [retrieved on 11 April 2003]. Retrieved from the Internet: <URL: http://www6.ipdl.jpo.go.jp/Tokujitu/PAJdetail.ipdl?N0000=60&N0120=01&N2001=2&N3001=2002-079125> Abstract, paras [0021]-[0027], fig 1	1, 2, 11-18, 27-31
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex		
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>		
Date of the actual completion of the international search 26 June 2003		Date of mailing of the international search report 03 JUL 2003
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustalia.gov.au Facsimile No. (02) 6285 3929		Authorized officer G.M. COX Telephone No : (02) 6283 2178

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU03/00745

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>JP 2001-205245 A (CANON CHEMICALS INC) 31 July 2001 See machine translation [online], [retrieved on 11 April 2003]. Retrieved from the Internet: <URL: http://www6.ipdl.jpo.go.jp/Tokujitu/PAJdetail.ipdl?N0000=60&N0120=01&N2001=2&N3001=2001-205245> Abstract, paras [0009]-[0010], fig 1</p>	1, 2, 4-6, 8, 10-12, 16-18, 20-22, 24, 26, 27, 29-31
A	<p>JP 2001-300331 A (SHINOHARA TEKKO LTD) 30 October 2001 See machine translation [online], [retrieved on 11 April 2003]. Retrieved from the Internet: <URL: http://www6.ipdl.jpo.go.jp/Tokujitu/PAJdetail.ipdl?N0000=60&N0120=01&N2001=2&N3001=2001-300331> Abstract, paras [0007], [0012], [0023], figs 1 & 8</p>	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/AU03/00745

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
US	6311904	EP	978318	FR	2782023	JP	2000051730
JP	2002079125	NONE					
JP	2001205245	NONE					
JP	2001300331	NONE					
END OF ANNEX							

Box No. VIII (iv) DECLARATION: INVENTORSHIP (only for the purposes of the designation of the United States of America)
The declaration must conform to the standardized wording provided for in Section 214; see Notes to Boxes Nos. VIII, VIII (i) to (v) (in general) and the specific Notes to Box No. VIII (iv). If this Box is not used, this sheet should not be included in the request.

Declaration of inventorship (Rules 4.17(iv) and 51 bis.1(a)(iv)) for the purposes of the designation of the United States of America:

I hereby declare that I believe I am the original, first and sole (if only one inventor is listed below) or joint (if more than one inventor is listed below) inventor of the subject matter which is claimed and for which a patent is sought.

This declaration is directed to the international application of which it forms a part (if filing declaration with application).

This declaration is directed to international application No. PCT/AU03/00745 (if furnishing declaration pursuant to Rule 26ter).

I hereby declare that my residence, mailing address, and citizenship are as stated next to my name.

I hereby state that I have reviewed and understand the contents of the above-identified international application, including the claims of said application. I have identified in the request of said application, in compliance with PCT Rule 4.10, any claim to foreign priority, and I have identified below, under the heading "Prior Applications," by application number, country or Member of the World Trade Organization, day, month and year of filing, any application for a patent or inventor's certificate filed in a country other than the United States of America, including any PCT international application designating at least one country other than the United States of America, having a filing date before that of the application on which foreign priority is claimed.

Prior Applications:

I hereby acknowledge the duty to disclose information that is known by me to be material to patentability as defined by 37C.F.R. § 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the PCT international filing date of the continuation-in-part application.


I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name: Stephen MORRISS

Residence: Victoria, Australia
(city and either US state, if applicable, or country)

Mailing Address: 15 John Street, Eltham, Victoria 3095, Australia

Citizenship: Australian Citizen

Inventor's Signature: 
(if not contained in the request, or if declaration is corrected or added under Rule 26ter after the filing of the international application. The signature must be that of the inventor, not that of the agent)


Date: 07.07.03
(of signature which is not contained in the request, or of the declaration that is corrected or added under Rule 26ter after the filing of the international application)

Name: Graham BADMAN

Residence: New South Wales, Australia
(city and either US state, if applicable, or country)

Mailing Address: C/- Brentwood Recycling Systems, 238 Berkeley Road, Unanderra, New South Wales 2526, Australia

Citizenship: Australian Citizen

Inventor's Signature: 
(if not contained in the request, or if declaration is corrected or added under Rule 26ter after the filing of the international application. The signature must be that of the inventor, not that of the agent)

Date: 17/07/03
(of signature which is not contained in the request, or of the declaration that is corrected or added under Rule 26ter after the filing of the international application)

☒ This declaration is continued on the following sheet, "Continuation of Box No. VIII (iv)".

Continuation of Box No. VIII (i)

DECLARATION

Received 24 July 2003

If the space is insufficient in any of Boxes Nos. VIII (i) to (v) to furnish all the information, including in the case where more than two inventors are to be named in Box No. VIII (iv), in such case, write "Continuation of Box No. VIII..." (Indicate the item number of the Box) and furnish the information in the same manner as required for the purposes of the Box in which the space was insufficient. If additional space is needed in respect of two or more declarations a separate continuation box must be used for each such declaration. If this Box is not used, this sheet should not be included in the request.


Continuation of Box No. VIII(iv)

Name: Jim BADMAN

Residence: New South Wales, Australia
(city and either US state, if applicable, or country)

Mailing Address: C/- Brentwood Recycling Systems, 238 Berkeley Road, Unanderra, New South Wales 2526, Australia

Citizenship: Australian Citizen

Inventor's Signature: 
(if not contained in the request, or if declaration is corrected or added under Rule 26ter after the filing of the international application. The signature must be that of the inventor, not that of the agent)

Date: 17. 07. 03
(of signature which is not contained in the request, or of the declaration that is corrected or added under Rule 26ter after the filing of the international application)